

SOLO™ IBS Back-Up Siren

SOLO siren is perfect solution for local alarm signal of a modern alarm control system. Due to its own backup battery it can work in case of wire tamper. Sound power of the siren is tremendous, changing weather has no effect for the proper operation. Double housing of the siren (outside ABS, inside metal housing) provides high protection against tampering.

Features

- Outdoor usage, double housing (external ABS, inside metal housing)
- Resin spilled weatherproof electronics
- Tamper protection (against wire tampering, opening, removing)
- Alarm control panel- or self operated tamper protection
- Positive or negative siren starting
- Service input to disable siren from alarm control panel
- Flashing lamp control input (to signal armed status of system)
- Siren flashing lamp trouble output
- Limited current consumption from external power (max. 750 mA)
- Visual and acoustic test at power-up
- Easy installation with drill plate (opening or separable cover)
- CE declaration, ISO 9001:2009 certificate
- Made in EU, proven quality



Technical data

Product	SOLO IBS
Power supply	13.8 ± 0.3 V DC
Maximum current consumption	max. 2 A
Standby current consumption	max. 60 mA
Max. current from external power supply	max. 750 mA
Backup battery	12V 7.0 Ah
Sound pressure at 1m	120 dB (A)
Case protection level	IP34
Operating temperature	-30 °C / +50 °C
Sizes (W / L / H)	180 x 90 x 270 mm
Weight (without battery)	2000 g

